

10/538326

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



538326

(43) International Publication Date
24 June 2004 (24.06.2004)


PCT

(10) International Publication Number
WO 2004/053528 A1

- (51) International Patent Classification⁷: **G01V 3/12**
- (21) International Application Number:
PCT/US2003/039309
- (22) International Filing Date:
10 December 2003 (10.12.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/432,467 10 December 2002 (10.12.2002) US
- (71) Applicant (for all designated States except US): **THE REGENTS OF THE UNIVERSITY OF CALIFORNIA** [US/US]; 1111 Franklin Street, 5th Floor, Oakland, CA 94607 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **CONSTABLE, Steven, C.** [US/US]; 5295 Bothe Ave., San Diego, CA 92122-4018 (US).
- (74) Agents: **MUSICK, Eleanor, M.** et al.; Procopio Cory Hargreaves & Savitch LLP, 530 B Street, Suite 2100, San Diego, CA 92101-4469 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: SYSTEM AND METHOD FOR HYDROCARBON RESERVOIR MONITORING USING CONTROLLED-SOURCE ELECTROMAGNETIC FIELDS



(57) Abstract: The system and method for real-time monitoring of a hydrocarbon reservoir (4) during extraction include an electromagnetic source assembly (16) for transmitting a first plurality of electromagnetic fields. A plurality of seafloor antennae (30a-30d) is distributed over an area of the seafloor (8) corresponding to the reservoir (4), where each antenna (30a-30d) comprises a receiver electrode array (30a-30d) adapted for receiving a second plurality of electromagnetic fields and generating signals corresponding to the detected fields. A data logging processor receives the signals over time and stores data corresponding to the signals. Different combinations of the receiver electrode are used in combination with transmitter antennae for measuring vertical, radial and/or azimuthal fields. Transmission and detection of the fields can be performed continuously or at timed intervals during hydrocarbon extraction to estimate the rate and efficiency of extraction.

WO 2004/053528 A1